



KANOMAX
The Ultimate Measurements

Anemomaster™ LITE

Palm-size and feather-weight standard hot-wire anemometer

Anemomaster™ LITE is a compact and lightweight hot-wire anemometer unit. It offers research-grade accuracy at an affordable, industry competitive price. It comes in a dark metallic blue casing with anti-slip.

Applications

- HVAC Testing
- Facility Maintenance
- Critical Environment Certification
- IAQ Investigations



Features

- Weighs only 180g and is a very compact unit.
- Research quality at a contractor-friendly price.
- Extended 2 year warranty.
- Single switch operation in a comfortable ergonomic design
- The probe easily detaches from the main unit and can be replaced in the field.
- Includes 4 pcs. AA batteries, carrying case, and NIST Certificate.



Anemomaster™ LITE Specifications

Air Velocity:	Range	0.01 to 20.0 m/s
	Accuracy	+/- 5.0% of reading or 0.015 m/s whichever is greater
	Resolution	0.01 m/s (0.01 to 9.99 m/s), 0.1 m/s (10.0 to 20.0 m/s)
Temperature:	Range	-20 to 70°C
	Accuracy	0.5°C
	Resolution	0.1°C
Power Supply:		4 x AA batteries
Operation Range:	Main Unit	5 to 40°C with no visible condensation
	Probe	-20 to 70°C with no visible condensation
	Storage	-10 to 50°C with no visible condensation
Weight:		180 g
Dimensions:	Main Body	60 x 120 x 34 mm
	Probe	Probe Length: 205 mm)
		Probe Diamter of Tip: 6.1 mm
Warranty:		2 years

Specifications are subject to change without notice.

KANOMAX JAPAN, INC.

2-1 SHIMIZU
SUITA, OSAKA 565-0805 JAPAN
TEL: +81-6-6877-0183
FAX: +81-6-6877-5570
E-mail: sales@kanomax.co.jp
URL: www.kanomax-usa.com

Distributed by: